



民承电子  
MC-Power

# 承认书

## APPROVAL SHEET

客户名称  
CUSTOMER

型号  
MODEL

MDG3S04C065

出厂确认:

拟制 PRODUCED BY	审核 CHECKED BY	批准 APPROVED BY
冯宝龄	宋韦辰	杨红伟

客户确认:

确认 CONFIRM	审核 CHECKED BY	批准 APPROVED BY

## Applications

- Switch Mode Power Supply
- Power Factor Correction
- Solar Inverter
- Uninterruptible Power Supply

## Features

- No Reverse Recovery/ No Forward Recovery
- Temperature Independent Switching Behavior
- Positive Temperature Coefficient on  $V_F$
- Fast Reverse Recovery
- High Surge Current Capability

## Benefits


- Higher System Efficiency
- System Cost and Size Savings
- High Frequency Operation
- Higher System Reliability
- Reduced EMI

## Product Summary

$V_{RRM}$	650	V
$I_F@T_C=150^\circ\text{C}$	4	A
$V_{F,TYP}@T_C=25^\circ\text{C}$	1.5	V
$V_{F,TYP}@T_C=175^\circ\text{C}$	1.8	V
Qc	8.5	nC



## DFN5x6



Cathde: 5-8

Anode: 1-3

## Package Marking and Ordering Information

Ordering code	Marking	Package	Packaging	Min. package quantity
MDG3S04C065	MDG3S04C065	DFN5x6	Tape & Reel	5000

**»» Absolute Maximum Ratings (Tc=25°C unless otherwise noted)**

Parameter	Symbol	Ratings	Unit
Peak Repetitive Reverse Voltage	$V_{RRM}$	650	V
Surge Peak Reverse Voltage	$V_{RSM}$	650	V
DC Peak Blocking Voltage	$V_R$	650	V
Continuous Forward Current Tc=150°C	$I_F$	4	A
Non-Repetitive Peak Forward Surge Current	$I_{FSM}$	35	A
Power Dissipation	$P_D$	50	W
Junction Temperature	$T_j$	175	°C
Storage Temperature	$T_{stg}$	-55-175	°C

**»» Thermal Characteristics**


Parameter	Symbol	Max	Unit
Maximum Junction-to-Case	$R_{\theta JC}$	3	°C/W
Maximum Junction-to-Ambient	$R_{\theta JA}$	60	°C/W

**»» Electrical Characteristics (Tc=25°C unless otherwise noted)**


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static Parameters</b>						
DC Blocking Voltage	$V_{DC}$	$I_R=100\mu A$	650	-	-	V
Forward Voltage	$V_F$	$I_F=4A$	-	1.5	1.7	V
		$I_F=4A, T_J=175^\circ C$	-	1.8	2.3	V
Reverse Current	$I_R$	$V_R=650V$	-	0.5	10	$\mu A$
		$V_R=650V, T_J=175^\circ C$	-	10	50	$\mu A$
<b>AC Parameters</b>						
Total Capacitive Charge	$Q_C$	$I_F=4A,$ $dI/dt=500A/\mu s,$ $V_R=400V, T_J=25^\circ C$	-	8.5	-	nC
Total Capacitive	C	$V_R=1V, f=1MHz$	-	135	-	pF
		$V_R=200V, f=1MHz$	-	17	-	
		$V_R=400V, f=1MHz$	-	16	-	




Characteristics Curves




Forward Characteristics




Reverse Characteristics



Capacitance



Recovery Charge vs. Reverse Voltage



Current Derating



» DFN5x6 Package Dimensions

Unit: mm

Symbol	Min	Nom	Max	Symbol	Min	Nom	Max
A	0.90		1.10	k	1.15		1.35
A3	0.15		0.30	b	0.20		0.40
D	4.90		5.10	e	1.15		1.35
D1	3.90		4.10	L	0.50		0.65
D2	4.75		5.05	L1	0.43		0.55
E	5.85		6.15	H	0.55		0.68
E1	3.35		3.55	$\theta$	8°		12°
E2	5.55		5.85				

